




Fob



Disc



Thick / Clamshell Card



Thin / ISO Card

## RFID/Prox Credentials

ZKAccess RFID/Prox credentials can be used with any ZKAccess readers which have a built-in 125 KHz prox card reader.

**Note** When ordering ZKAccess readers, be sure to specify which card reader technology and cards you need PRIOR to placing your order.

For customers already using existing non-ZKAccess card readers and cards, ZKAccess also provides 125 KHz key fobs which can be clipped on to existing customers' cards having a badge clip slot. And for customers having non-ZKAccess cards with no badge clip slot, we also offer 125 KHz self-adhesive RFID discs.

### Specifications

#### Interface

EM-4100 series prox cards with a EM/Marin S.A. memory chip.

#### 125 KHz (generic prox)

26-bit, Read-only

#### 13.56 MHz (Mifare)

Read-only

#### Passive prox/RFID responder

### Dimensions

#### Key Fob size:

1.37 inches x .91 inches x .15 inches  
34.8 mm x 23mm x 3.9 mm

#### Thick Clamshell Card

**Length:** 3.36 inches (85.47 mm)  
**Width:** 2.12 inches (53.85 mm)  
**Thickness:** .077 inches (1.97 mm)  
**Badge clip slot:** 0.63 inches X .13 inches

#### RFID disk size:

**Diameter:** 7/8 inch (22.22mm)  
**Thickness:** 1/16 inch (1.59mm)

#### Thin ISO card

**Length:** 3.36 inches (85.47 mm)  
**Width:** 2.12 inches (53.85 mm)  
**Thickness:** 0.03 inches (0.8 mm)  
**Badge clip slot:** 0.63 inches X 0.13 inches  
(16 mm X 3.30 mm)

Design and Specifications subject to change without notice

## ZKAccess

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004

Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com